



FOLDING/JOINING MACHINE . MX 211 / 212 SE

Machine for folding or joining the edge of a fabric to which a two-sided adhesive tape has already been applied. The machine is fitted with an additional heater and a blade nozzle to heat the area inside the join or the folding effectively.


The machine performs following functions:

Folding: easy to realize folding edges in continuous (an adhesive tape has to be applied first).


Joining: easy to join fabrics in continuous (an adhesive tape has to be applied first).

HIGHLIGHTS

- Increasing of productivity (speed up to 20 m/min)
- Step back feature
- Siliconed rubber conveyor belt
- Can deal also with curves
- Possibility to operate on open and closed garments
- Low and easy maintenance
- Reduced size



APPLICATIONS



FOLDED EDGE

A first step is required to apply a double sided adhesive tape



SIMPLE JOINING

A first step is required to apply a double sided adhesive tape



JOINING WITH REDUCED FOLDED EDGE

A first step is required to apply a double sided adhesive tape

TECHNOLOGY





FOLDING/JOINING MACHINE . MX 211 / 212 SE

FEATURES

- New blower (reduced air and power consumption)
- Speed up to 20 m/min
- Even heat distribution - No scorched fabrics
- Low and easy maintenance
- Tapes of different quality and widths can be used
- Maximum load: 11 kg
- Minimize electricity consumption
- Greater performance with less quantity of air



HEAT HAS NEVER BEEN SO GREEN
less consumption, better efficiency

Average consumption for standard applications

Electricity consumption: 0.45 kw/h

CO₂ emission: 129 gr/h

Compressed air consumption: 45 to 55 l/min

TECHNICAL INFO FOR INSTALLATION

Dimension and weight

875 x 535 x H.1370 mm - 65 Kg

Pneumatic connection

- Fast junction diam 8 mm
- Maximum air flow: 100 l/min -
- average consumption: 45 - 500 l/min
- Input air pressure: 5.5 bar (0.55 MPa)
- Air quality: dry air in accordance to DIN 8573-1
- with dew point + 3° C not lubricated

Electric connection

- Nominal voltage: 230 Vac
- Nominal frequency: 50 Hz / 60 Hz
- Nominal power requirements: 2200 W

BASE MACHINE DESCRIPTION

- Base machine with 2 heater
- Table support structure
- Pneumatic foot switches
- Protection screen
- Horizontal harm
- Spot lamp
- Beek nozzle for folding or joining
- Folding guide 8 mm
- Joining guide PTFE coated
- Shaped rubber wheel 24/12 mm 35 sh (soft) - folding
- Rubber silicone wheel 17 mm - 35 sh (soft) - joining
- 30 mm nozzle
- 16A 3 poles plug

Specifications and appearance are subject to change without prior notice for improvement