

Mini (Table-top) Fusing Press

MP400TS - MP600TS



SPECIFICATIONS

- ◆ 40 or 60 cm fusing widths
- ◆ Maximum 2.5 kg/cm² pneumatic pressure
- ◆ One-side-open design enables working with large pieces
- ◆ Accurate temperature control with digital PID Control System (±%1)
- ◆ Belt tracking with Static Control System
- ◆ Mobile design with large working table
- ◆ Mesh Cooling Conveyor with Fan at exit (Optional)
- ◆ Waistband unwinding and winding mechanism (Optional)

Maxi Fusing Press

MXP600



SPECIFICATIONS

- ◆ 60 cm Fusing width
- ◆ Even pneumatic pressure up to 6 kg/cm²
- ◆ Top and bottom heating zones with individual digital controls
- ◆ Accurate temperature control with digital PID Control System (±%1)
- ◆ Belt tracking with Static Control System developed by Konsan
- ◆ Anti-Pleating rollers for removing air bubbles
- ◆ Worktop and feeding belt at entry
- ◆ Mesh Cooling Conveyor with Fan at exit
- ◆ Castors for mobility
- ◆ Return-to-operator belt instead of cooling fan at exit (Optional)

Technical Specifications

	Resistance Power	Fusing Width	Maximum Temperature	Pressure	Maximum Belt Speed	Fusing Time	Machine Width	Machine Length	Machine Height	Machine Weight	Electricity	Average Consumption
MP400TS	3.5 kW	40 cm	200 °C	2.5 kg/cm ²	10 m/min	5-30 sec	101 cm	140 cm	41 cm	105 kg	220 VAC veya 380 VAC	2.7 kW
MP600TS	6 kW	60 cm	200 °C	2.5 kg/cm ²	10 m/min	5-30 sec	120 cm	200 cm	45 cm	115 kg		4.0 kW
MXP600	11.2 kW	60 cm	200 °C	6 kg/cm ²	11 m/min	5-40 sec	96 cm	260 cm	140 cm	360 kg	380 VAC 50 Hz	7.0 kW

KONSAN İÇ VE DİŞ TİCARET LTD. ŞTİ.

10016 Sokak. No. 70
Çiğli, İzmir - TÜRKİYE

info@konsan.tech

Phone: +90.232 328 31 41
Fax: +90.232 328 31 44

www.konsan.tech



INTERNATIONAL SALES OFFICE
KONSAN UK LIMITED

20 Tysoe Gardens SALFORD
M3 6BL UNITED KINGDOM

info@konsan.co.uk

Phone: +44(161) 834 87 00
Fax: +44(161) 834 28 72